"CUSTOM" DEEP WATER REELS

MANUAL, ELECTRIC, HYDRAULIC & GEAR DRIVEN

Frames & Stanchions on all models are constructed from 11/4" schedule stainless steel pipe. Stanchions are complete with a welded foot mount, stainless steel gunwale mount bracket and "T" type locking bolt. Heavy duty 5/8" diameter stainless steel spool shaft. Retrieving rate: Electric model: 500"/ min., no load = 6 amps draw; 350'/min. moderate to heavy load = 30 amps draw.

GEAR DRIVEN REEL

12 Volt - 3/4 HP

ELECTRIC REEL 12 Volt - 1/4 HP

MANUAL REEL



ITEM NUMBER **SNRCGBER** \$ 2,382.95



ITEM NUMBER SNRCER \$ 1,799.95



ITEM NUMBER **SNREM** \$ 931.95

HYDRAULIC MODEL AVAILABLE (NOT PICTURED)

ITEM NUMBER SNRCHR \$ 1.944.95

UPGRADE TO AN ALUMINUM SPOOL FOR MONO-FILAMENT USE, ADD \$270.00 TO PRICE

ITEM #SNRCAS58 5/8" FOR MANUAL & ELECTRIC REEL

ITEM #SNRCAS1 1" FOR 12 Volt GEAR DRIVEN & HYDRAULIC REEL



- DRAG & FREE SPOOLING FEATURE ON ALL MODELS
- SPOOL CAPACITY FOR ALL MODELS: 3/64" CABLE 3500' +
- FIBERGLASS BOOM ON ALL MODELS
- HYDRAULIC AND GEAR DRIVEN REELS USE 1" DIA. SPOOLS
- ELECTRIC AND MANUAL REELS USE 5/8" DIA. SPOOLS
- ALL REELS EQUIPPED w/HEAVY DUTY PLASTIC SPOOL; UPGRADE TO ALUMINUM SPOOL AVAIL.
- FRAME SLIDES INTO STANCHION FOR EASY REMOVAL AND SWIVEL ACTION
- WEIGHT: MANUAL REEL 24 LBS., ELECTRIC REEL 40 LBS., HYDRAULIC REEL 40 LBS.



Atlantic & Gulf Fishing Supply Corp.







Sales: (305) 888-9646, (800) 327-6167

Fax: (305) 888-6027

Email: sales@atagulf.com Please visit our website located at http://www.atagulf.com for current pricing and information.